

BGC FIBRE CEMENT - NZ

1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PRODUCT NAME	BGC Fibre Cement Sheets
OTHER NAMES	Duraliner Plus / Durasheet / Duratex / Duralattice / Duralux Plus / Duraplank / Ultraform / Compressed / Ceramic & Tile Underlay / Vinyl and Cork Underlay / Nuline Plus / Duracom / Duragrid / Durascape / Duragroove / Stonesheet / Stratum / Stratum Duo / Stratum Duo Offset / Stratum Trio / Stratum Contour / Durafloor / DurabARRIER / Intergroove / Duracom Greystone Charcoal / Duracom Greystone Natural / Duracom Greystone Basalt / Durascape Greystone / Durapanel / Duracom Earthstone Quartzite / Duracom Earthstone Anthracite / Duracom Earthstone Ochre
UN NUMBER	None Allocated
DANGEROUS GOODS CLASS & SUBSIDIARY RISK	None Allocated
HAZCHEM CODE	None Allocated
POISONS SCHEDULE NUMBER	None Scheduled
USE(S)	Fibre cement sheets for use on internal/external wall linings and soffits and internal/external flooring. Refer to product manual for installation.
COMPANY	BGC (Australia) Pty Ltd T/A BGC Fibre Cement
ADDRESS	77 Cryers Rd, East Tamaki, Auckland 2013
WEBSITE	www.bgcinnovadesign.co.nz
TELEPHONE	09 273 1457
FAX	09 273 1461
EMERGENCY PHONE NUMBER	111 Fire Brigade, Police and Ambulance
POISON INFORMATION CENTRE	0800 764 766

2 - HAZARDS IDENTIFICATION

The potential health hazards are related to dust generated from these materials during cutting, sanding and the use of power tools.

The intact BGC Fibre cement products do not give off dust or fume during installation or when installed. However, cutting, breaking, drilling, sanding, rebating or sawing the boards may generate dust. Inhaling dust liberated from BGC Fibre cement may aggravate pre-existing respiratory conditions and may cause cancer.

Smoking and inhalation of airborne particulates from other sources may increase the risk of lung disease.

Work areas and storage areas should be deemed smoke-free zones.

GHS CATEGORY	PICTOGRAM	SIGNAL WORD	HAZARD CODE	HAZARD STATEMENTS
Carcinogenicity, Cat 1A		Danger	H350	May cause cancer through inhalation of dust
Specific target organ toxicity (repeated exposure), Cat 1		Danger	H372	Causes damage to respiratory system through prolonged or repeated exposure

OTHER CLASSIFICATIONS Contact with dust and fibres from this product may cause skin and eye irritation due to physical reaction (e.g. rubbing or scratching).

PRECAUTIONARY STATEMENTS Observe the following precautionary measures when handling, installing or processing the product.

BGC FIBRE CEMENT - NZ

Prevention Precautionary Statement Codes

CODE	PRECAUTIONARY STATEMENT
P201	Obtain special instruction before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe in dust.
P264	Wash hands and face thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P281	Use personal protective equipment as required.

Response

P308+P313	If exposed or concerned: get medical advice.
P314	Get medical advise if you feel unwell.

Disposal

P501	Dispose products in accordance with local/region/national/international regulations.
------	--

3 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	PROPORTION	EXPOSURE LIMITS
Calcium silicate hydrate	66997-15-1	40%-60%	10.0 mg/m ³ measured as inspirable dust
Crystalline silica	14808-60-7	20%-60%	0.05 mg/m ³ measured as inspirable dust
Paper pulp (cellulose)	9004-34-6	< 10%	10 mg/m ³ measured as inspirable dust
Calcium silicate aluminat	21645-51-2	< 5%	10 mg/m ³ measured as inspirable dust
Water		< 15%	
Other non-hazardous ingredients (pigments, sealers, coatings)		< 5%	

4 - FIRST AID MEASURES

SWALLOWED	Give copious amounts of water to drink to dilute stomach contents. Wash mouth and lips with water. Do not induce vomiting. If symptoms persist, seek medical attention.
EYE	Remove contact lens or eyeglasses. Flush thoroughly with flowing water for at least 10 minutes. If redness persists, seek medical attention.
SKIN	Wash thoroughly with soap and water. Contact physician if irritation persists or later develops.
INHALED	Remove to fresh air.
ADVICE TO DOCTOR	Treat symptomatically.

5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS	BGC Fibre Cement products are non-flammable and non-combustible.
SUITABLE EXTINGUISHING SUBSTANCES	Not applicable.
UNSUITABLE EXTINGUISHING SUBSTANCES	Not applicable.
PRODUCT OF COMBUSTION	BGC Fibre Cement products are non-combustible and non-flammable.

BGC FIBRE CEMENT - NZ

6 - ACCIDENTAL RELEASE MEASURES

SPILL AND DISPOSAL	Use wet sweeping and/or vacuuming to clean up dust and waste. Dry sweeping should not be attempted. Vacuuming with an M or H class industrial vacuum is recommended. Do not wash material down storm water drains. Bagged waste should be placed in containers and disposed of with other construction waste in accordance with local authority guidelines.
--------------------	---

7 - STORAGE AND HANDLING

STORAGE	Fibre cement sheets should be stored flat and level in a covered dry area. Avoid contact with strong acids and strong oxidizing agents.
HANDLING	Crystalline silica dust may be generated during processing and handling. Use appropriate personal protective equipment to reduce exposure to respirable silica dust. Keep dust generation to a minimum using proper tools. Wear protective equipment to prevent skin and eye contamination. Manual handling should be in accordance with Manual Handling Regulations and Codes. Maintain the work area clean by using wet sweeping or vacuuming with an M or H class filter. Keep fibre cement from incompatible materials. Read and understand all safety precautions before handling fibre cement.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE STANDARDS	<p>BGC Fibre Cement has adopted the following maximum exposure limits, corresponding to the limits set out by the CoA, NOHSC; Exposure Standards for Atmospheric Contaminants in the Occupational Environment:-</p> <ul style="list-style-type: none"> • Calcium silicate: 10 mg/m³ time-weighted average (TWA) as inspirable dust • Cellulose: 10 mg/ m³ TWA as respirable dust • Crystalline silica (quartz): 0.05 mg/ m³ TWA as respirable dust <p>BGC Fibre Cement recommends keeping exposures to dust as low as practicable and work in a well-ventilated space.</p>
ENGINEERING CONTROLS	<p>Keep exposures to dust as low as practicable. Refer to the exposure standards for maximum limits. Cutting, sanding, rebating, drilling, grinding and other machining activities will generate dust. Power tools should be fitted with a local dust extraction device with a HEPA M or H class filter. Hand tools (unpowered) generate less dust when cutting or sanding. If generated dust cannot be avoided, follow recommendations for protective equipment.</p> <p>Work in the open air or near external openings in the building, for adequate ventilation. Where dust is generated, in confined spaces, local mechanical ventilation should be used, to direct the dust away from the work areas.</p> <p>Personal protective equipment should be used in confined spaces and where dust levels exceed the maximum levels.</p> <p>Use safe work practices to minimize dust release and exposure.</p> <p>Clean work areas regularly by wet sweeping or vacuuming with a HEPA class M or H filtered vacuum. Never attempt dry sweeping as it excites silica dust into the workers' breathing zone.</p>
VENTILATION	<p>Where safe work practices, adequate engineering and material handling controls are in place, ventilation is not normally required.</p> <p>Use local mechanical ventilation and or dust extraction in confined areas and where dust could escape into the working environment.</p>
TOOLS AND EQUIPMENT-	
REPAIR AND MAINTENANCE	<p>Vacuum and or wipe down all tools and equipment prior to maintenance and repair work. Avoid compressed air cleaning where possible, follow recommended exposure controls and protective equipment as listed below.</p>
SKIN PROTECTION	<p>Avoid direct skin contact with fibre cement products.</p> <p>Wear loose appropriate clothing, such as long sleeved shirts and long trousers, head protection and standard duty leather or equivalent gloves, which comply with Australian Standard AS 2161: Industrial Safety Gloves and Mittens.</p> <p>Wash work clothes regularly and do not shake out dust.</p>
EYE PROTECTION	<p>Wear dust resistant non-fogging safety goggles or glasses, which comply with Australian and New Zealand Standard AS/NZS 1336: Recommended Practices for Eye Protection.</p>

BGC FIBRE CEMENT - NZ

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION cont.

RESPIRATORY PROTECTION	BGC Fibre Cement recommends particulate respirator, which comply with Australian and New Zealand Standard AS/NZS 1715: Selection, Use and Maintenance of Respiratory Protective Devices, and Australian and New Zealand Standard AS/NZS 1716: Respiratory Protective Devices when Exposed to Dust), be used at all times. The type of respirator to be used will depend on the level of exposure determined through sampling. If in doubt about the exposure level, use a respirator that offers the highest protection from respirable silica.
PERSONAL HYGEINE	Do not eat, drink, or smoke whilst handling and working with fibre cement. Wash dust from skin with mild soap and water after working with fibre cement.
FLAMMABILITY	Fibre cement products are non-combustible and non-flammable.

9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Factory applied blue tint on face of the Duratex™, and a white tint to the face of 4.5, 6.0, 9.0 and 12mm Compressed while all other products are cement grey finish.	BOILING POINT (°C)	Not Applicable
VAPOUR PRESSURE	Not Applicable	SPECIFIC GRAVITY (H ₂ O = 1)	Not Relevant
FLASH POINT	Not Applicable	FLAMMABILITY LIMITS	Not Flammable
SOLUBILITY IN WATER	Not Relevant	REACTIVITY (I.E. WITH WATER OR AIR)	Not Reactive
AUTO-IGNITION TEMPERATURE (°C)	-	ODOUR THRESHOLD	Slight cement odour
LOWER EXPLOSION LIMIT	-	UPPER EXPLOSION LIMIT	-
SELF ACCELERATING DECOMPOSITION	-		

10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY	Stable and non-reactive.
HAZARDOUS REACTIONS	None
CONDITIONS TO AVOID	Dust generation during handling, processing and inhalation.
INCOMPATIBLE MATERIALS	Strong acids and strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS	None

11 - TOXICOLOGICAL INFORMATION

Health Effects: Acute (short term)

SWALLOWED	Unlikely to occur, however may result in symptoms of acute indigestion.
EYES	Excessive dust may cause eye irritation.
SKIN	The dust, particularly in association with heat and sweat, can cause irritation, but it is not absorbed through skin.
INHALED	Inhaled dust may cause nasal, throat and lung irritation, symptomatic through excess mucus and coughing.

Health Effects: Chronic (long term)

INHALED	If respirable crystalline silica levels are not controlled, repeated exposure to excessive dusts of fibre cement products could result in chronic lung disease silicosis. However, if the practices noted in this SDS are followed during cutting and sanding, exposure to airborne dusts should be within recommended occupational exposure standards and no long-term effects are expected.
---------	---

BGC FIBRE CEMENT - NZ

12 - ECOLOGICAL INFORMATION

ECO-TOXICITY	BGC Fibre Cement products are not toxic to aquatic and terrestrial organisms.
PERSISTENCE AND DEGRADABILITY	No data
BIOACCUMULATIVE POTENTIAL	No data
MOBILITY IN SOIL	A low mobility would be expected in a landfill situation.

13 - DISPOSAL CONSIDERATION

DISPOSAL	BGC Fibre Cement products must be disposed into a landfill site in accordance with local authority guidelines. Measures should be taken to prevent dust generation during disposal, and exposure and personal precautions should be observed (see above).
----------	---

14 - TRANSPORT INFORMATION

TRANSPORT	No special transport requirements are necessary.
-----------	--

15 - REGULATORY INFORMATION

Not scheduled.

16 - OTHER INFORMATION

For further information on this product, please contact:
 BGC (Australia) Pty Ltd (ABN 6200 5736 005 008) T/A BGC Fibre Cement
 77 Cryers Rd, East Tamaki, Auckland 2013
 Phone: 09 273 1457
 Fax: 09 273 1461

ADDITIONAL INFORMATION

Australian Standards References

AS/NZ 1336	Recommend Practices for Occupational Eye Protection
AS/NZ 1715	Selection, Use and Maintenance of Respiratory Protective Devices
AS/NZ 1716	Respiratory Protection Devices
AS 2161	Industrial Safety Gloves and Mittens (excluding electrical and medical gloves)

Other References

NOHSC:1008 (2004)	Approved Criteria for Classifying Hazardous Substances
MODEL CODE OF PRACTICE	Preparation of Safety

AUTHORISATION

REASON FOR ISSUE	Add new product names in Section 1. Updated Section 2, 3 and 8.
DATE OF ISSUE	August 2023

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us or any loss or damage cause by any person acting or refraining from action as a result of this information.